Certificate of Location of Government Corner

ID#: 410607 **Description:** NW SEC COR 6 41 **Date Set:** 1875 **County:** Fillmore

Section: 06 **Township:** 104N **Range:** 11W **Monument Description:** 6" x 6" square cap on iron monument

Reference Ties:

The corner falls 1' NE of car frame corner post to fence north and west
Survey marker sign and post 1" south of monument
County survey disk in east side of brace post North, 11.1'
PK nail in east side brace post NNE 32.0'

Corner History:

6-1853 John Ball, Deputy Surveyor, set a post for corner during the original Public Land Survey.

10-1853 Fillmore County gov't plat shows the NE corner of Section 1-104-12 is 56 links (36.96') west of the south quarter of 36-105-12.

1875 John Gregor, Deputy Surveyor, was commissioned to set the NE corner of each township with a 2 1/2" x 2 1/2" x 30" solid iron bar with 6" square iron plate on top

8-15-1974 Fillmore County Surveyor found a 2 1/2" x 2 1/2" x 30" solid iron bar with 6" square iron plate on top. Fillmore County Certificate of Location Doc. No. 373481

2-28-2005 Olmsted County survey crew found 6"x6" square iron plate down 0.2' at the NE corner section 1-104-12, Fillmore County. Post with sign broken off, remnants up 0.5' and 0.2' to the south.

4-15-2011 Joel Thoreson, Olmsted County Surveyor, visited the area of the corner and found no monuments or occupation lines at the south quarter corner of section 36-105-12. Found iron bar with 6"x6" iron top at the NE corner of section 1-104-12. The monument is 1' NE of a car frame used as a fence corner with fences north and west. Computed a location for the south quarter corner of section 36 by using midway distance from the SW corner of 36 and the SE corner of 36 and on a line from the SW corner of 36 through the found monument at the NE corner of section 1-104-12. The computed location is 31.63' east of the iron monument at the NE corner of section 1-104-12.