Certificate of Location of Government Corner

ID#:420206 **Description:** 1/4 SEC COR 2 3 42 **Date Set:** 10/1/1895 **County:** Fillmore

Section: 02 **Township:** 104N **Range:** 12W **Monument Description:** 1 1/2"x2 1/2" topped iron bar

Reference Ties:

The corner falls on NW side of CP to fences N-S-E

Corner History:

10-1853 Gov't Notes Phipps and Fitzpatrick, Deputy Surveyors 40.00 chs. Set quarter section post. Elm 10 in. N57 1/2°W25 lks. Elm 8 in. N56°E 12 lks. 79.94 chs. intersect boundary at post. 12-1886 Thomas Hunter, Olmsted County Surveyor, (Old Field Book 14, Page 75) "found witness trees standing and also stub of old stake in ground--distance from NW bearing tree was 23 lks. instead of 25 per Field Notes." He set a property corner 16.25 chs. North on line to N Sec. 2-3 39.65 chs. North. 10 & 11-1895 O.H. Case, Fillmore County Surveyor, (P. 110 Fillmore County Books) states "Bearing tree of the U.S. notes standing and plant iron post for the corner." Measure North 39.60 chs. to N Sec. Corner 2-3. 11-1895 O.H. Case, Fillmore County Surveyor (P. 110, Fillmore County Books) used this corner to set the Center 3, T104N, R12W. 8-14-1979 Olmsted County Surveyor found a 1 1/2"x2 1/2" topped iron bar standing on the NW side of the corner post to fences N-S-E. Left iron as found.