Certificate of Location of Government Corner

ID#: 420607 **Description:** NW SEC COR 6 42 **Date Set:** 6/3/1981 **County:** Fillmore

Section: 06 **Township:** 104N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #8952

Reference Ties:

The monument is down 1.1'
The corner falls 6' north of centerline of E-W twp road and 4' west of centerline twp road south
Chisel cross in N end 60" culvert ENE 38.91'
Chisel cross in S end 60" culvert SE 57.01'
Chisel cross in W end 60" culvert SW 69.54'
This corner is located by GPS measurement.

Corner History:

6-1853 Gov't Notes: Elisha Norris, Deputy Surveyor; North between sections 1 & 6. 79.67 chs. Intersect 1st Standard Parallel 286 links west of quarter section corner to section 36 and set post corner. Built mound with trench. NE planted apple see and drove charred stake at center.

1875 State law required monuments to be set at township corners.

9-1893 William Fraser, County Surveyor, (Bk.A Pg.530 No.494) measured from the NW corner section 6 to this corner.

6-3-1981 Olmsted County Surveyor found a 2" square iron with 6" square plate w/raised lettering. Set 1" square pipe at road surface and over iron found. See Fillmore County Certificate of Location Doc. No. 374607

10-28-2010 Olmsted County survey crew found 1" sq. pipe with cap in good condition.