# Certificate of Location of Government Corner

**ID#:**420609 **Description:** 1/4 SEC COR 2 3 42 **Date Set:** **County:** Fillmore

**Section:** 02 **Township:** 104N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1 1/2" x 2 1/2" topped iron bar standing on the NW side of the corner post to fences N-S-E

**Reference Ties:**

**Corner History:**

10-1853 Gov't Notes Phipps and Fitzpatrick, Deputy Surveyors 40.00 chs. Set quarter section post. Elm 10 in. N571/2º 25 lks. Elm 8 in. N56ºE 12 lks. 79.94 chs. Intersect boundary at post.

12-1886 Thomas Hunter, Olmsted County Surveyor, (Old Field Book 14, Page 75) "found witness trees standing and also stub of old stake in ground--distance from N.W. bearing tree was 23 lks. Instead of 25 per Field Notes." He set a property corner 16.25 chs. North on line to N. Sec. 2-3 39.65 chs. North.

10&11-1895 O.H. Case, Fillmore County Surveyor, (P. 110 Fillmore County Books) states "Bearing tree of the U.S. notes standing and plant iron post for the corner." Measured North 39.60 chs. To N. Sec. Cor. 2-3.

11-1895 Case (P. 110, Fillmore County Books) used this corner to set the Center 3, T104N, R12W.

8-14-1979 The Olmsted County Surveyor found a 1 1/2" x 2 1/2" topped iron bar standing on the N.W. side of the corner post to fences N-S-E. Left iron as found.