Certificate of Location of Government Corner

ID#: 430407 **Description:** N SEC COR 4 5 43 **Date Set:** 6/23/1981 **County:** Fillmore

Section: 04 **Township:** 104N **Range:** 13W **Monument Description:** Chiseled cross in large granite boulder

Reference Ties:

The corner falls under fence south
This corner is located by GPS measurement

Corner History:

9-1853 E.S. Norris, Deputy Surveyor, set a 12" x 12" x 4" stone for the corner during the original Public Land Survey

1893 William Fraser, Surveyor, found nothing at this corner and set a stone in the lost position between found stones to the east and west. He calls for a stone 18" x 8" x 4".

6-23-1981 Fillmore County Surveyor searched for 18" x 8" x 4" stone set by Fraser in 1893. The search area is dominated by an extremely large granite boulder buried at the fence corner. No trace of a stone even vaguely resembling the size of the one set by Fraser could be found. However, the stones at the S 1/4 and SW corner of Section 32, T105N, R13W were found and an "X" was chiseled in the top of the granite boulder on line between those stones and a PLS distance of 137.28 feet west of the S 1/4 corner of said Section 32. Fillmore County Certificate of Location Doc. No. 374610

8-17-2009 Olmsted County Surveyor found stone w/chiseled X down 0.3' in good condition. Corner Post is lying flat next to stone, fences south and east still there but down at corner.