Certificate of Location of Government Corner

ID#: 430607 **Description:** NW SEC COR 6 43 **Date Set:** 11/21/2012 **County:** Olmsted

Section: 06 **Township:** 104N **Range:** 13W **Monument Description:** Cast iron Cap on Telspar Pipe

Reference Ties:

The monument is at the surface.
The corner falls 1' south of CP to fences east and south
Sign on CP 1/2' south
This corner is located by GPS reference stations "Bovine A & B"

Corner History:

1853 Gov't Notes Interested 1st Standard Parrallel 211 links west of 1/4 section corner of section 36. Built a mound, trench, charred stake, and planted seeds.

1875 State law required monuments to be set at township corners. Thomas Hunter is believed to have set a limestone monument although no survey notes exist.

5-1902 W. Fraser (Book B, Pg. 16) found the corner. 16 west set stone M & L 20.66'. 16 south set stone, 16 center NE 1/4 1 set corner.

9-17-1971 Olmsted County Surveyor found the engraved limestone monument.

1-15-1974 David Knutson, Fillmore County Surveyor, found 11x10x36 stone monument. Fillmore County Certificate of Location Doc. No. 374715

5-17-1995 Olmsted County Surveyor found engraved stone monument at twp corner 1' north of corner post to fence south and east. Nail & sign on north face of corner post.

8-6-2002 Olmsted County Surveyor found engraved stone monument in good condition.

11-21-2012 Olmsted County survey crew found 11"x10"x36" engraved limestone in good condition. Removed and replaced with a 5' telspar pipe with cast iron cap at the surface.