Certificate of Location of Government Corner

ID#:440306 **Description:** 1/4 SEC COR 3 4 44 **Date Set:** 11/15/2011 **County:** Olmsted

Section: 03 **Township:** 104N **Range:** 14W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls 11' east of N-S fence and 1' north of fence east
Spike in brace post NW 13.4'
Spike in 10" post W 10.4'
Center brace post SW 12'
This corner is located by GPS measurement
Post with sign 2' east

Corner History:

1853 Gov't Notes Ball; 40.0 set 1/4 section post and deposited charcoal and raised mound of earth and sod and planted osage orange seeds east and west between pits and trench.

4-1875 Corner in controversy.

5-1878 T. Hunter Pg.343 No.337; found stake in mound & pits. Moved stake north to settle dispute and make gov't measure more nearly correct by strong testimony of Mr. Knapp and Staples avering that stake at corner right and original so moved corner back as found.

1-1902 W. Fraser Pg.29B; found stone set at corner of fence by post.

8-1-1974 County Surveyor set 4" square concrete monument.

11-1995 Roger Brand found 4" square concrete monument. Set 5/8" conduit on north side of concrete monument. RPs-Spike in brace post NW 13.4', Spike in 10" post W 10.4', Center brace post SW 12'.

11-13-2001 County Surveyor found 4" square concrete monument up 0.2' in good condition.

11-15-2011 County survey crew found 4"x15" concrete monument in good condition. Removed and replaced with a 5' telspar pipe with cast iron cap.