Certificate of Location of Government Corner

ID#:440406 **Description:** 1/4 SEC COR 4 5 44 **Date Set:** 8/8/1974 **County:** Olmsted

Section: 04 **Township:** 104N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 1' north of field entrance west
Minnesota Highway Disk in PP NE 40.56'
NW corner 6" square TCM box SW 48.21'
Minnesota Highway Disk in PP NW 45.67'
Fence post E 33.09'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes North on true line between sections 4 and 5. 40.00 chs. Set quarter section post. Made mound with trench pit from which a stone 4x6 feet S23°E 37 lks. Deposited charcoal.

5-1878 Thomas Hunter (P. 343 No. 337), County Surveyor, found large boulder which had been set in exact place of original stake.

4-1906 Charles Armstrong (P. 104 Book B), County Surveyor, found recorded corner. RPs- 1/2" rod over stone and stake found, disc fence post E 33.45', disc TP SW 50.95'. Corner is PI for road north.

1931 County Highway Department (Book 61 P. 25) had hub over stone.

1940 County Highway Department (Book 112 P. 1) had 1/2" rod over stone and stake found.

5-1950 John Kerr (Book 46 P. 72), County Surveyor, used corner for line west.

6-22-1971 County Surveyor found rod used as corner. Dug and found numerous hubs and nails and 4 or 5 small boulders. (Evidently large boulder had been removed.) RPs- MHD in power pole NW 45.67', NW corner fence post E 33.09', MHD in PP NE 40.56'.

8-8-1974 County Surveyor set a CIM over a 1/2"x12" rod in place of rod found.

11-06-2001 County Surveyor found CIM down 0.4' in good condition.

9-29-2005 County Surveyor found CIM down 0.5' in good condition.

5-15-2007 County Surveyor found CIM down 0.5' in good condition.