Certificate of Location of Government Corner

ID#:440505 **Description:** SEC COR 5 6 7 8 44 **Date Set:** 10/19/1972 **County:** Olmsted

Section: 05 **Township:** 104N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 6' south of centerline of twp road east
Punch mark in S end 24" CMP SE 40.63'
Top center N end 24" CMP NE 43.4'
Punched cross in S end 30" CMP ESE 84.88'
Punched cross in N end 30" CMP ENE 88.23'
This corner is located by GPS measurement

Corner History:

6-1878 T. Hunter Pg.348 No.341, Armstrong; G.J.Cavil avers in 1866 that he set a red cedar post 6x6x40" in old stake hole in the bog and on digging 2' deep found a foot of old post. Set new post and stone 7-1-1900 by Armstrong.

1900 C. Armstrong (unrecorded Survey) found a 6" by 6" by 40" red cedar stake claimed set by the pioneer settlers in 1866 in a bog. About 1/3 of the post remains and the person who set the post was present when the survey was done. Charlie set a boulder 16" by 18" by 24" with a red cedar post 5" by 5" by 36" in the place of the orig. gov't stake.

1940 Olmsted county highway department; Stake in road. RPs- spike TP NE 44.2', spike corner fence post SE 48.2'.

12-8-1971 Olmsted County Surveyor found a large boulder with cross. Found stone 6.3' south and 4.9' west of iron in tile.

10-19-1972 Olmsted County Surveyor set CIM over 12" galv bolt. Removed conc tile & rod. No further RPs.

5-18-1995 Olmsted County Surveyor found CIM down 0.6' in good condition.

3-19-2002 Olmsted County Surveyor found CIM down 0.6' in good condition.