Certificate of Location of Government Corner

ID#:440605 **Description:** W SEC COR 6 7 44 **Date Set:** 5/30/1979 **County:** Olmsted

Section: 06 **Township:** 104N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 13' east of fence south and 3' north of E-W fence
County Survey Disk in SE side blazed 9" Bur Oak NE 19.78'
County Survey Disk in SW side blazed 9" Bur Oak SE 23.23'
Post w/sign 1' south
This corner is located by GPS reference stations "Lecy A & B"

Corner History:

7-1853 Gov't Notes John Ball, Deputy Surveyor We do not have these notes in our records; however, Thomas Hunter, a County Surveyor in the 1800's here, records the witness trees as: Bur Oak 10 in. N36°E 80 links. Bur Oak 10 in. N45°W 59 links.

6-4 & 5-1878 Thomas Hunter, County Surveyor, (BK. A, Page 348, No. 341 and Old Field Book 5, Page 73) "Found stake not marked standing near fence post--tested it by the witness trees both of which were standing and found stake correct." He used this corner to set the W 1/4 corner 6 on line and at prorated Gov't measure to the NW corner 6.

6-7 to 10-1878 T. Hunter (B,. A, Page 350, No. 342 and Old Field Book 5, Page 75) found corner as described in Survey No. 341. Measured 39.35 chains West to the S 1/4 corner 1.

6-1885 T. Hunter (Bk. A, Page 398, No. 388 and Old Field Bk. 14, Page 42) "found old stake standing and tested it by witness trees both still standing and found it correct." He set a large boulder stone, small end up, midway (19.68 1/2 chains) and on line at the 1/16th West.

Appx. 1900 Charles Armstrong (Old Field Book 11, page 31) located corner by two Burr Oaks which are still standing. Used this corner to set the E 1/4 corner 1 on line to NE corner 1 and 40.12 chains North of the SE corner 1.

1940 A. Armstrong (County Highway Department Bk. 109, Page 76) measured North from the fence corner at this corner in a survey to set the E 1/4 corner 1.

5-30-1979 Olmsted County Surveyor projected the line and doubled the measure from the S 1/4 corner 1 (found) over Hunter's boulder (found) at the 1/16th East and dug. Dound the remains of a stake standing on the NE side of a large black mark in clay which appears to have been the former location of a post. The stake had decomposed to wood fragments but by shaving down the side we could see where it had been sharpened to a point. We drove a 12" piece of steel fence post I the stake hole and set a Cast Iron Cap on a piece of square pipe (telspar) over it. Measure West 2596.78' to the S 1/4 corner 1 and North 2642.40' to the E 1/4 corner 1. Set survey marker sign and post .9' south. The corner is 13' east of the fence south and 3' north of the E-W fence and came very near the calc. Location. RPs-Spike and CSD in SE side blazed 9" Bur Oak NE 19.78', Spike and CSD in SW side blazed 9" Bur Oak SE 23.23'.

11-9-2000 Olmsted County Surveyor found cast iron cap on telspar pipe up 0.3' in good condition.