Certificate of Location of Government Corner

ID#:440609 **Description:** SEC CEN 6 44 **Date Set:** 3/29/2005 **County:** Olmsted

Section: 06 **Township:** 104N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CSAH 6 and 1 1/2' west of centerline of twp road south
County Survey Disk in NE side PP NW 69.17'
This corner is located by GPS measurement

Corner History:

6-4-1878 Hunter set a limestone 2" by 8" by 18" at the intersection of the lines from all 1/4 corners with the 1/16th west being a 3" by 10" by 22" limestone

4-1911 Charles Larson Pg.156 B; Found corner in road.

1927 Bk.48 Pg.17; Found boulder 15" wide LS on north side. RPs- Spike fence post NW 70.2', spike TP NE 28.7'.

1940 county highway department found a boulder and set a 3/4" iron riser. RPs- 1 1/2" pipe N 33.07'. Disc in TP #400 NE 42.6', disc in TP #419 SE 77.9'.

11-4-1971 County Surveyor found the recorded limestone. Removed boulder and set 5/8"x16" rod over L stone. RPs-70.28' SW to a punched cross in the W end of a 24" galv. Culv. 72.3' SE to a punched cross in the E end of a 24" galv. Culv. 56.4' SW to a bottle cap on the SE side of PP #10574. 42.0' N.E. to a County Highway Department disc in TP No. 400/2. 40.0' N. to an 1 1/4 pipe with steel fence post beside it.

9-27-1996 McGhie & Betts found and used 5/8" iron at center of section 6.

5-14-2003 County Surveyor referenced location, removed 5/8" iron rod.

3-29-2005 County Surveyor set 1" square pipe w/cap at surface from reference angle. CSD with concrete nail in NE side of PP (no #) NW 69.17'. Monument falls 1 1/2' west of twp road south and in centerline of CR 6.

9-27-2007 County Surveyor found 1" square pipe w/cap at surface in good condition.