Certificate of Location of Government Corner

ID#:450104 **Description:** 1/4 SEC COR 1 12 45 **Date Set:** 5/25/1979 **County:** Olmsted

Section: 01 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 8' east of N-S fence
County Survey Disk in E side 7" blazed Burr Oak S 3.07'
County Survey Disk in N side 5 1/2" blazed Burr Oak E 5.37'
County Survey Disk in crotch 16" blazed Burr Oak NNW 15.78'
Post with sign 1 1/2' south
This corner is located by GPS reference stations "Lecy A & B"

Corner History:

1853 Gov't Notes, Ball; West on true line between sections 1 & 12, 39.975 set 1/4 section post. RPs- 13" black oak S53 E 21 links, 14" black oak N10 W\353 links.

8-1853 Gov't Notes, John Quigley, Deputy Surveyor; West on true line between sections 1 & 12, 39.97 1/2 chs. RPs- 13" black oak S53°E21 links, 14" black oak N10°W353 links. 79.95 to section corner.

6-1878 T. Hunter Pg.350 No.342; Found stake standing in fence and part of SE bearing tree standing which proved stake as true corner. Tested stake and found it to correspomd with the field notes. Set the center 1 a 18"x8"x5" boulder.

6-1885 T. Hunter Pg.398 No.388; Found remains of stake in ground under fence with stone by its side. Tested by witness tree and found correct. 16' east set large boulder stone, small end up M & L 19.685' set for line north.

5-1979 Olmsted County Surveyor (remon Bk. Pg.59, 71) found shattered boulder and wood pieces in black mark. Drove a 1" square by 30" pipe in center of the mark and drove a square pipe with CIC over 1" pipe as corner. Found Hunter's boulder at the 1/16 east. RPs- Corner is 8' east of the present N-S fence and approx. 10.3' East and 16.0' north of the traverse nail, spike & CSD in E side 7" blazed burr oak S 3.07', spike & CSD in N side 5 1/2" blazed burr oak E 5.37', spike & CSD in crotch 16" blazed burr oak NNW 15.78', burr oak NNE 13 1/2".

5-17-1979 Olmsted County Surveyor 1/16 east Pg.59; Set spike as traverse point in SW side of corner post to fences N & E.

5-25-1979 Olmsted County Surveyor found a 10x12x26 boulder down 6" approx. 14' east and 1.5' south of the traverse nail by the corner post. Set a piece of an old drag on the NW side of the stone and a 3/4"x3 1/2' shaft found standing up 1' and 6' east of the traverse nail for the corner at Hunter's measure from the S 1/4 corner 1 just found.

11-9-2000 Olmsted County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition.