Certificate of Location of Government Corner

ID#: 450107 **Description:** N SEC COR 1 2 45 **Date Set:** 6/13/1979 **County:** Olmsted

Section: 01 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 42 1/2' east of fence south and 4 1/2' south of E-W fence
County Survey Disk in E side 22" Burr Oak SE 161.93'
County Survey Disk in NE side blazed 9" Elm NW 44.45'
County Survey Disk in SE side blazed 14" Burr Oak SSW 11.32'
Post w/sign 3' north
This corner is located by GPS reference stations "Higgins A & B"

Corner History:

1853 Gov't Notes, John Ball, North on true line between sections 1 & 2; 78.10 intersected 1st Standard Parallel 490 links west of 1/4 section post corner on south boundary of section 35. RPs- 16" burr oak S77 W255 links, 14" elm N84 E256 links

6-23-1877 T. Hunter (Book A, Pg.320 No.314) Corner gone, but bearing tree stumps plain which set corner exactly the same. Set stake marked.

6-7-1878 T. Hunter (Book A, Pg.350 No.342) found stake set from bearing tree stumps. 16 east set stake, 16 south set stake, 16 center NW 1/4 set stake.

6-15-1895 W.Fraser, County Surveyor (Book A, Pg.637 No.574) Found stake set p320. Set new stake & 2 stones by its side one on top of the other and stake 2-3' south and east of corner post of fence. 16 west set stake & boulder.

5-17-1979 County Surveyor dug and found 2 pieces of limestone.

6-13-1979 County Surveyor set CIM over 1/2"x2' rod on standard parallel on line from south corner Section 34-35 105-15 to south quarter corner 35-105-15 and south of stone found (0.92'). Survey sign is 2.8' north. RPs- spike & CSD in SE side blazed 14" burr oak in fence line S SW 11.32', spike & CSD in east side 22" burr oak SE 161.93', spike & CSD in NE side blazed 9" Chinese Elm NW 44.45'.

11-2-2000 Olmsted County survey crew found CIM down 0.7' in good condition.

1-29-2013 Olmsted County Surveyor computed a new corner location on the standard parallel by intersecting the west line of Section 1-104-15 with the south line of section 35-105-15. The computed position is 0.04' north of the inplace cast iron monument.