Certificate of Location of Government Corner

ID#:450108 **Description:** N 1/4 SEC COR 1 45 **Date Set:** 6/6/1979 **County:** Olmsted

Section: 01 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls under E-W fence
County Survey Disk in NE side blazed 21" Black Oak WSW 20.97'
County Survey Disk in E side blazed 8" Burr Oak S 21.48'
County Survey Disk in NE side blazed 14" Black Oak SW 38.79'
Post with sign 1' north
This corner is located by GPS reference stations "Ironwood A & B"

Corner History:

6-1878 T. Hunter, Pg.350 No.342; Corner never set in original survey. Established corner midway NW cor 1 and NE cor 1 and on line NW cor 1 and SW corner 36 105 15. Tested SW BT and proved correct. 16 west set stake, 16 south set stake.

6-1885 T. Hunter Pg.398 No.388; Found stake set by me in survey No.342.

2-1895 W.Fraser Og.574 No.525; Used this corner to set S sec cor 35-36, a stake and stones, 4.80 chains east as recorded by Hunter and on line to the NE cor. 1.

6-1971 County Surveyor found small limestone.

6-6-1979 County Surveyor set a square pipe with CIC. Corner is .13' south of the stone found 6-18-1971. Put stone on the north side of the CIC on pipe. Survey sign 1' north. RPs-spike & CSD disc in NE side blazed 21" black oak WSW 20.97', spike & CSD disc in E side blazed 8" burr oak S 21.48', spike & CSD disc in NE side 14" blazed black oak SW 38.79'.

11-7-2000 County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition.