Certificate of Location of Government Corner

ID#:450204 **Description:** 1/4 SEC COR 2 11 45 **Date Set:** 11/17/2005 **County:** Olmsted

Section: 02 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2' east of fence north and in line with fence east
Sign on fence post 0.3' east
This corner is located by GPS reference stations "Vaupel A & B"

Corner History:

1853 Gov't Notes, Ball; West on true line between sections 2 & 11 39.99 set 1/4 section post. RPs- 10" burr oak N51 E222 links, 11" burr oak N64 E229 links.

6-1877 T. Hunter Pg.320 No.314; B trees gone. Found stake at junction of 2 fences avered by Mr. Crumb as true corner. 16 north set stake, 16 center SW 1/4 2 set stake.

6-1895 W.Fraser Pg.637 No.574; Used west side of corner post as it was on line of N 1/4 2 over center 2.

5-22-1979 Olmsted County Surveyor remonumentation Bk. Pg.64; Shot spike .9' SSE of the corner post to fences E-W-N.

2000 Olmsted County Surveyor computed location for use by Wayne Koski Surveying in SW 1/4.

10-23-2002 Olmsted County Surveyor dug to locate corner post used by W. Fraser in 1895. Dug 4 1/2' N-S x 5' E-W x 2' deep hole centered on existing iron corner post. C.P. is imbedded in concrete down 3' deep. Dug to clean clay. Found nothing.

11-17-2005 Olmsted County Surveyor set 4' telspar pipe w/cast iron cap up 0.3' at computed position from GPS and traverse data.