Certificate of Location of Government Corner

ID#:450205 **Description:** SEC COR 2 3 10 11 45 **Date Set:** 6/12/1979 **County:** Olmsted

Section: 02 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 6 1/2' west of centerline of N-S twp road, 10' south of fence east and 12 1/2' south of fence west
County Survey Disk in SE side PP #24860 SW 76.95'
County Survey Disk in S side CP NW 28.04'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, John Ball, north between sections 10 & 11; 80.0 set post for corner to sections 2-3-10-11. Made mound with trench and put handfull of small stones in center and planted osage orange seeds in SE corner.
Gov't Notes, John Quigley, Deputy Surveyor, north on true line between sections 2 & 3; 40.0 chs set quarter section post and built mound with trench per instructions. Drove charred stake in center and planted osage orange seed in SE corner on south boundary of section 34.

6-21-1877 T. Hunter Pg.319 No.313; Found mound with stake remains in center and impression of one pit. Set new marked stake in place.

6-23-1877 T.Hunter Pg.320 No.314; found described corner. 16 north set stake, 16 center SW 1/4 2 set stake.

6-1895 W. Fraser Pg.637 No.574; Corner gone. Retraced line of Hunter Pg.319 in setting 1/4 2-3. After setting W 1/4 from line east pushed line south of 1/4 2-3. Meas of 39.66' NW 2 to W 1/4 2 now 39.64' 1/2 so made W 1/2 2 to SW 2 39.98'. Meas. S 1/4 3 to S 1/4 2 which put corner on line from N. Set stake as corner which came 15 links south & 10 links west of corner post of fences running east and south. 16 north set stake and boulder, 16 center SW 1/4 2 set iron stake.

6-12-1979 Olmsted County Surveyor found 2" square stake 20" long. Drove a 1"x38" pipe in the stake hole with a 1/2"x34" iron on top of the pipe. Set a CIM at the road surface. Corner is 6 1/2' west of centerline, 10' south of fence east and 12 1/2' south fence west and 10.2' south and 5.1' west of the traverse nail. RPs- CSD in SE side pp# 24860 SW 76.95', CSD in South side corner post NW 28.04'.

6-29-2000 Olmsted County Surveyor found CIM in good condition.