Certificate of Location of Government Corner

ID#:450207 **Description:** N SEC COR 2 3 45 **Date Set:** 6/12/1979 **County:** Olmsted

Section: 02 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4 1/2' south of the PP line east
County Survey Disk in S side PP #24845 NE 14.04'
Post w/sign 1' north
The corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Ball; 78.64 Intersected 1st Standard Parallel 500 links west of 1/4 section corner on south boundary of section 3 twp105 N range 15 w 5TH. Principle Meridian. Made mound with trench and drove charred stake in center and planted apple tree seed in NW corner.

6-1877 T. Hunter, Pg.319 No.313; Set marked stake at section corner south 33-34. Set stake at S 1/4 34, then as NE 3 set stone 5x10x15. Also set marked stake at N 1/4 3.

6-12-1979 County Surveyor set CIM over iron with large boulder on the south side of the CIM and a Survey marker sign .85' ENE. The corner is 4 1/2' south of the pp line east. RPs- CSD south side pp# 24845 NE 14.05'.

8-10-1995 County Surveyor found CIM in good condition. Post & sign destroyed. Set new sign & post 1' north of CIM. Tie to pp# 24845 is now 14.04'.

12-7-2000 County Surveyor found CIM down 0.2' in good condition.