Certificate of Location of Government Corner

ID#:450304 **Description:** 1/4 SEC COR 3 10 45 **Date Set:** 11/17/2005 **County:** Olmsted

Section: 03 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in line with fence north and in line with E-W fence rows
Post w/sign 2' south
This corner is located by GPS reference stations "Deer Stand A & B"

Corner History:

1853 Gov't Notes, Ball, West on true line between sections 3 & 10; 39.965 set 1/4 section post. Made mound with trench and drove charred stake in center and planted osage orange seeds in SE corner.

6-1877 T. Hunter, Pg.319 No.313; Found mound and pits, but no stake. Set new stake.

10-1885 T. Hunter Caption to 319; Replaced corner with boulder stone on east side of stake. 16 west stone on north side of stake.

10-15-2002 Olmsted County Surveyor dug to locate T. Hunter stake and stone position. Many stone boulders and much sediment from Southwest field made this deep fill area. Found only post mark with wood posts running 1' deep into hard mixed up clay, very little original top soil. The post mark started at 3 1/2' deep running to 4 1/2' deep. Referenced post location.

11-17-2005 Olmsted County Surveyor set 5 1/2' telspar pipe w/cast iron cap over 120d spike set at post mark location up 0.2'. Set post w/sign.