Certificate of Location of Government Corner

ID#:450308 **Description:** N 1/4 SEC COR 3 45 **Date Set:** 11/14/2011 **County:** Olmsted

Section: 03 **Township:** 104N **Range:** 15W **Monument Description:** Cast iron cap on telspar pipe

Reference Ties:

The monument is up 0.2'
The corner falls 2.5' south of E-W fence.
This corner is located by GPS reference stations "Hamilton A & B"

Corner History:

6-1877 T.Hunter Pg.319 No.313; Corner never set. Set marked stake. NW 3 boulder found and avered as corner. NE 3 boulder 3x10x15 5 chains west of S 1/4 34. N 1/4 3 lies 4.89 chs. West of SW corner 34 called "N" which was set midway between SE 34 & SW 33 80.26 for each half, but not on line, but 40.25 south from 1/4 33-34. The legal limit of overrun sec line south of NE cor. 3 south overruns 1 chain. From this corner lines straight to SE 34 and SW 33 sto stake set at N 1/4 3 online SE 33 to SW 33.

9-24-2002 County Surveyor dug 6'x6' hole centered on spot 11.7' West and 2.3' South of fence post shot to cover area from old c.p. at South sec. cor 33-34 105-15 and West Fraser's full measure. Down at 0.3' found old c.p. to fence S-E-W 11.5' West of fence post at 1.0' deep found 2"x3"x12" stake tapered to a point at 10.3' West of fence post. Continued digging down to 2.5' deep and found nothing further. All black dirt in bog area.

12-16-2002 Olmsted County Surveyor computed a location of the corner for Olmsted County Right of Way Plats 136 and 137. Position was computed on a line from the south quarter of Section 33-105-5 to the southeast corner of Section 33-105-5 and using Thomas Hunter's distance of 4.89 chains (322.74') from said southeast corner. No monument was set.

11-14-2011 County survey crew set 5.5' telspar pipe with cast iron cap at the 2002 computed coordinate location.