Certificate of Location of Government Corner

ID#: 450404 **Description:** 1/4 SEC COR 4 9 45 **Date Set:** 11/29/2012 **County:** Olmsted

Section: 04 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is at the surface
The corner falls in the east-west fence line
Post with sign 2' East
This corner is located by GPS measurement

Corner History:

1853 Gov't notes, Ball, west on true line between sections 4 & 9; 40.015 set 1/4 section post. Made mound with trench & drove charred stake in ceter and planted osage orange seeds in SE corner.

6-11-1878 T.Hunter Book A, Pg.351 No.343; Found mound and pits, but no stake so drove new stake in center of mound.

10-30-1895 W.Fraser Book A, Pg.584 No.533; Found stake and left as found. 16 west drove stake, 16 east found stake.

? Used this corner in this survey to set SW corner 4 so meas. From SW 4 west to S 1/4 5 same as above from SW 4 to S 1/4 4.

11-23-1993 Olmsted County Surveyor dug for stake beside fence post used by W. Fraser in 1895. Found many boulders but no evidence of a stake or post hole.

12-16-2002 Olmsted County Survey Department staff computed a corner location for Highway Right of Way Plat No. 135 by projecting the North Quarter of Section 4 through the center of Section 4 and line of fence east-west.

11-29-2012 Olmsted County survey crew set a 5' telspar pipe with cast iron cap at the computed position used for Olmsted County Highway Right of Way Plat No. 135