Certificate of Location of Government Corner

ID#: 450405 **Description:** SEC COR 4 5 8 9 45 **Date Set:** 12/11/2012 **County:** Olmsted

Section: 04 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on Telspar Pipe

Reference Ties:

The monument is down 0.3'
The corner falls in line with E-W fence and common line north.
Set post 2' North

Corner History:

1853 Gov't Notes, Ball, north between sections 8 & 9; 80.0 set section post. Made mound with trench and put charred stake in center and planted osage orange seeds in SE corner.

10-1895 W.Fraser (Book A, Pg.584 No.533) Corner stake remians found after meas from 4 ways. Drove new stake and set boulder by its side. 16 north and east set stake.

6-1898 W.Fraser (Book A, Pg.633 No.572) found corner set.

11-29-2012 Olmsted County survey crew visited the area and found that it was recently excavated and cleared. Spoke with the property owner who said he buried a large stone pile that had accumulated over the years.

12-5-2012 Olmsted County survey crew dug an area 2' North, 7' South and 2 East and West of corner fence post. Found many stones but the area was recently disturbed by farming activities, no other evidence was found. Olmsted County surveyor decided to accept the fence corner post as the section corner location. This falls within 2' of W. Fraser's double proportion location.

12-11-2012 Olmsted County survey crew set 6' telspar pipe with cast iron cap at corner post location.