Certificate of Location of Government Corner

ID#:450408 **Description:** N 1/4 SEC COR 4 45 **Date Set:** 11/19/93 **County:** Olmsted

Section: 04 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in E-W fence
Post w/sign 1' north

Corner History:

6-1878 T. Hunter Pg.351 No.343; Corner never set. Established corner midway between section corners. Set 1/16 corners east and west.

7-1893 W.Fraser Pg.521 No.487; Found stake. Replaced with boulder 6x8x16 in place of stake. Corner lies 4.71 1/2 west of stone 6x6x18.

10-1895 W.Fraser Pg.584 No.533; Found corner.

9-1935 county highway department Bk.79; Set 2x2 stake. 16 west found boulder and stake. RPs- cor fence post E 27.8, fence post NE 39.5, fence post NW 39.6.

10-1935 county highway department measured 2641.2 west from NE corner sec 4 and found limestone to north 1/4 corner of 4 and found remains of old stake on east and west fence lines.

1935 county highway department Bk.75 Pg.79; Found error in measurement (N 1/4 to NE cor.) went to NW corner of section 4 and measured across to NE corner section 4 which was 5289.6. Set 2x2 stake 1/2 way between the 2 corners or 2644.8 correct offsets on random line.

11-18-1993 County Surveyor found W. Fraser's 6x8x16 stone with stake. There is a + cut in top of stone. Set sign & post 1' north. Will set monument later.

11-19-1993 County Surveyor set CIC/square pipe .26' south of Fraser stone. Corner is under E-W fence with post & sign 1' north.