Certificate of Location of Government Corner

ID#:450507 **Description:** N SEC COR 5 6 45 **Date Set:** 11/8/1978 **County:** Olmsted

Section: 05 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 17' south of E-W fence and 8' north and 24' east of river bank
County Survey Disk in E side blazed 22" Burr Oak NNE 116.97'
County Survey Disk in NW side blazed Burr Oak NE 53.67'
Spike in S side Maple E 12.79'
Post w/sign 1' north
This corner is located by GPS reference stations "Blue Bells A & B"

Corner History:

1853 Gov't Notes Ball; 80.28 Intersected 1st Standard Parallel 536 west of 1/4 section corner on south boundary of section 31 twp 105N Rnage 15W 5th Meridian. RPs- 10" ash N1 E25 links, 10" burr oak S42 E185 links.

6-1875 T. Hunter Pg.285 No.282; Corner gone and all B trees. Found stump NE BT proving corner set. Drove stake well down.

6-1898 W. Fraser Pg.633 No.572; Corner gone. Relocated corner and set stake with 3 boulders on west side one on top of each other. S 1/4 31 stake in center of mound under E-W fence. Frove new stake & set boulder by its side in place of old stake.

11-7-1978 County Surveyor found 3 small boulders. Set stone back.

11-8-1978 County Surveyor set CIC over 6' square pipe. Corner came .18' N and .49' E of Fraser's boulder. Corner is 17' south of the E-W fence and 8' North and 24' east of the river bank. RPs- spike & CSD in E side blazed 22" burr oak NNE 116.97', spike & CSD in NW side blazed burr oak NE 53.67', spike in south side high maple E 12.79', survey marker sign and post 1.0' north.

5-4-2009 County Surveyor found cast iron cap on telspar pipe down 0.2' leaning WSW. All trees are still there but ties are gone/overgrown.