Certificate of Location of Government Corner

ID#: 450605 **Description:** W SEC COR 6 7 45 **Date Set:** 10/11/1988 **County:** Olmsted

Section: 06 **Township:** 104N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' south of centerline of township road west and 2' east of centerline of north-south township road (125th Ave SW)
The monument is down 0.5'
Bottle cap in power pole SW 46.52'
This corner is located by GPS measurement

Corner History:

7-15-1853 John Ball, Deputy Surveyor, measured north 80.00 chains between Sections 7 and 12. Set post for corner to Sections 1, 6, 7 and 12. RPs - 12" Burr Oak N28°W 341 links (225.06'), 5" Burr Oak S26°W 95 links (62.70'), 5" Burr Oak S10°E 36 links (23.76'), 5" Burr Oak N8°E 36 links (23.76')

8-15-1853 John Quigley, Deputy Surveyor, measured west 77.98 chains on random line, between Sections 6 and 7, for subdivision of Pleasant Valley Township. Intersected west boundary 20 links (13.20') north of post.

10-21-1853 John Fitzpatrick, Deputy Surveyor, measured east 80.50 chains on random line, between Sections 1 and 12, for subdivision of Sargeant Township. Intersected east boundary 7 links (4.62') south of post.

6-15-1875 Thomas Hunter, Olmsted County Surveyor, (Book A, Page 285. Survey No. 282), dug and found burr oak bark and small pieces of old stake in ground. Set new stake properly marked.

9-20-1988 Olmsted County Survey Crew dug and found 8"x11"x16" boulder stone along side top of stake down 2.7' in perfect condition.

10-11-1988 Olmsted County Survey Crew set Cast Iron Monument over 5/8" rod over stake found. The corner falls 2' south of centerline township road west and 2' east of centerline of north-south gravel road. RP - Bottle cap in power pole SW 46.52'

12-7-2000 Olmsted County Survey Crew found Cast Iron Monument down 0.5' in good condition and measured its position using GPS.