Certificate of Location of Government Corner

ID#:500606 **Description:** W 1/4 SEC COR 6 50 **Date Set:** 9/23/1998 **County:** Winona

Section: 06 **Township:** 105N **Range:** 10W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is up 0.4'
The corner falls in line with all old fences and between two large Box Elders
Post w/sign 1 1/2' east
This corner is located by GPS reference stations "Lundeen II & RDJ II"

Corner History:

6-22-1853 Gov't Notes: North 40 chins from SE cor. Set quarter post. BT's: Burr Oak 12" N75°W 19 links, Burr Oak 10" S20°E 23-1/2 links.

4-1892 Thos Fraser (P.476 No.455) found stake placed by settler on east, renewing old original stake a little north of corner post of fences N-S and W avered by a Mr. Barnes and other settlers. 1/16 west set stone, limestone 4x7x20 pointed on top M&L 19.95. 1/16 south set stone 4x10x28 M&L 19.92-1/2 with cross +. 1/16 center SE 1/4 1 set stone 3x8x22 at inters lines, no meas.

5-1900 Robt Fraser (P.674 No.455) found stake described P.476 at inters fences N-S-W a little north and a little west. Drove new burr oak stake and set stone 2x6x16 beside stake. 1/16 west found limestone at 19.95. 1/16 north drove stake M&L 20.02. 1/16 center NE 1/4 1 drove stake, no meas.

7-27-1998 Olmsted County Surveyor found stone lying flat that matches Robert Fraser stone size of 2" x 6" x 16". At 1/16th corner South we found stone 4" x 10" 28" with + on top set by Thomas Fraser in 1892.

9-9-1998 Olmsted County Surveyor dug for stake and stone in much tree roots 2 1/2' deep to clay line found nothing. Could make nothing of stone location from 7-27-1998.

9-23-1998 Olmsted County Surveyor set Cast Iron Cap on telspar pipe on section line between twp corner and 1/16th stone with + on top and in line of fence West.

10-25-2011 County survey crew found cast iron cap on telspar pipe in good condition