Certificate of Location of Government Corner

ID#:503005 **Description:** W SEC COR 30 31 50 **Date Set:** 6/9/2000 **County:** Winona

Section: 25 **Township:** 105N **Range:** 10W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' east of corner post to fences east, west and north
Sign on CP 1' west
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: N 80 chains, set post corner and dug trench. BT's: Burr Oak 14" N50°W 79 links. Burr Oak 12" S45°E 147 links. Burr Oak 11" N88°E 118 links.

5-1878 T. Hunter Bk.5 Pg.63 sec 36 unrecorded survey. Note shown at NE 36 at "a" found what said to be the stump of NE BT (the other gone) and aon measuring found it correspond with corner of old fence claimed to be where old sec corner stood. Meas west 79.78 to cor of fence.

6-8-2000 Olmsted County Surveyor dug for post area found by T. Hunter in 1878. Found post mark. Set 120d spike at surface over post mark.

6-9-2000 Olmsted County Surveyor set 5' telspar w/CIC at post mark location.

6-7-2004 Olmsted County Surveyor found cast iron cap on telspar pipe up 0.5' in good condition.