Certificate of Location of Government Corner

ID#:510105 **Description:** SEC COR 1 2 11 12 51 **Date Set:** 11/17/1998 **County:** Olmsted

Section: 01 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is down 1.5'
The corner falls in contour strip 25' east of strip between fields
This corner is located by GPS reference stations "Kjosa & Wava"

Corner History:

Gov't notes: stone set as corner (32"x9"x4") apparently no post set here, 8" Burr Oak N42E 114', 8" D. Oak S 71 1/2 E 109', 8" D. Oak S 45 1/2 E 233'

5-1889 Thomas Fraser pg 432 no 419 sec 12 found stone claimed by Mr.Strahn as set by his father 20 years before at site of original stake, measurement south 39.86 1/2 or 39.82 1/2 to 1/4 stone

11-1891 Thomas Fraser pg 462 no 446 sec 2 found stone pg 432. 1/16 west - set cedar stake on section line - midway, to 1/4 corner 40.02 chains.

4-1892 Thomas Fraser pg 476 no 455 sec 1 found stone pg 462. No measurement, no 1/16 corner.

4-1892 Thomas Fraser pg 477 no 456 found stone pg 476

11-17-1998 County Surveyor dug in plowed field for stone used in many surveys. Found nothing. Set Cast Iron Cap on telspar pipe down 1.5' in contour strip of hay at double line and distance from South.

12-6-2011 County survey crew found CIC in good condition