Certificate of Location of Government Corner

ID#: 510109 **Description:** SEC CEN 1 51 **Date Set:** **County:** Olmsted

Section: 01 **Township:** 105N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

4-6-1891 Thomas Fraser, County Surveyor, (Book A, Page 476, Survey No. 455) set unmarked stake at intersecting quarter lines. 1/16th South set temporary stake midway and on line at 20.04-3/4 chains (1323.14') to South 1/4. 1/16th East set 4"x7"x20" stone, pointed on top, midway and on line at 19.95 chains (1316.70') to East 1/4. 1/16th Center of SE 1/4 set 3"x8"x22" stone at intersecting sixteenth lines.

5-18-1900 Robert Fraser, Deputy County Surveyor, (Book A, Page 674, Survey No. 599) could not find corner. Ran line west from East 1/4 over 1/16th (found) and doubled distance & reset corner. 1/16th North set stake on line and at government proportionate distance to North 1/4. 1/16th East found limestone at 19.95 chains (1316.70') west of East 1/4. 1/16th West set stake midway and on line to West 1/4. 1/16th Center of NE 1/4 set stake at government proportionate sixteenth lines. 1/16th Center of NW 1/4 set stake at government proportionate sixteenth lines.

9-22-1998 County Survey Crew 1/16th East dug and found nothing.

10-1-1998 Roger Brand & Associates used computed center at intersecting quarter lines.

9-16-2016 Jerome Schwarz used computed center at intersecting quarter lines.