Certificate of Location of Government Corner

ID#:510204 **Description:** 1/4 SEC COR 2 11 51 **Date Set:** 9/5/1975 **County:** Olmsted

Section: 02 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 16' north of fence east and 13' east of fence south
County Survey Disk in N side gate post ESE 61.84'
County Survey Disk in NW side Oak CP SW 20.8'
County Survey Disk in NW side 24" Burr Oak SW 41.9'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes W.A. Jones, Deputy Surveyor West on true line between sections 2 and 11. 40.15 chs. Set quarter section post. Burr Oak 7" S68W 8 lks. Burr Oak 6" N881/2W 27 lks.

11-1891 Thomas Fraser (P. 462 No. 446), County Surveyor, states corne gone for years. Set temporary stake midway to establish N-S 1/4 line of Sec. 2.

4-1892 Thomas Fraser (pg 477 no 456) Set temporary point midway and on line.

9-5-1975 County Surveyor dug 4'x6' at computed corner location but found nothing. Set C.I.M. over 1/2" square by 12" spike at intersection on N-S 1/4 line of Section 2 and line from S.W. Cor. Sec. 2 to computed location of S.E. Cor. Sec. 2.

9-29-1998 County Surveyor found CIM set in 1975 in good condition in pasture down 0.3'.