Certificate of Location of Government Corner

ID#:510205 **Description:** SEC COR 2 3 10 11 51 **Date Set:** 9/28/1998 **County:** Olmsted

Section: 02 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 14 1/2' west of 24" Burr Oak tree used as CP to fences E-W-N
County Survey Disk in W side 12" Burr Oak N 43.05'
County Survey Disk in SE side 12" blazed Burr Oak NE 44.75'
Post w/sign 1/2' south
This corner is located by GPS reference stations "Grant & 510206"

Corner History:

9-1853 Gov't Notes William A. Jones, Deputy Surveyor 80.00 chs. Valley East and West and set post corner to sections 2,3,10, and 11. Burr Oak 12 in. N471/2E 104 lks. Burr Oak 15 in. N14W 184 lks. Red Oak 15 in. S44W 434 lks. White Oak 8 in. S8E 403 lks.

7-21-1975 County Surveyor found 4"x6"x30" limestone with chiseled cross on top up 12" on north side of old wood fence post in E-W fence line.

9-5-1975 County Sureyor set large bolt beneath stone and set railroad spikes on N. and E. sides.

9-28-1998 County Surveyor found long stone leaning badly. Dug out stone and set Cast Iron Cap on telspar pipe over large bolt set under stone in 1975. Note: found stones and iron a 1/16th corner West in good condition.