Certificate of Location of Government Corner

ID#:510305 **Description:** SEC COR 3 4 9 10 51 **Date Set:** 9/30/1998 **County:** Olmsted

Section: 03 **Township:** 105N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CSAH 30 and 1' north of centerline twp road west
County Survey Disk in PP NW 108.5'
Punch mark in N end CMP NW 40.01'
Punch mark in S end CMP SW 46.38'
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 9 and 10. 80.00 chs. Set post corner to sections 3,4,9,10. Burr Oak 7 in. N41/2ºE 608 lks. Burr Oak 8 in. S72ºE 161 lks. Burr Oak 7 in. S43ºW 331 lks.

4-1892 Thomas Fraser (P. 477 No. 456), County Surveyor, found a boulder in the road avered by a Mr. Colson as correct.

4-1892 Thomas Fraser (P. 483 No. 460) found the corner P. 477.

6-18-1976 County Surveyor dug in C.R. #30 and found a 9"x10"x15" boulder 7' deep with a 11/4" pipe driven on the East side.

6-22-1976 County Surveyor set a C.I.M. over a 1/2" iron rod over the stone as the corner.

10-27-1983 County Surveyor found CIM with head broken off.

9-30-1998 County Surveyor found CIM with top section broken off 14" deep in bituminous surface C.R. #30. Set 1" square pipe w/cap #15809 at CIM location.

7-23-2003 County Surveyor found 1" square pipe w/cap at surface in good condition.