Certificate of Location of Government Corner

ID#:510306 **Description:** 1/4 SEC COR 3 4 51 **Date Set:** 6/23/1976 **County:** Olmsted

Section: 03 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2 ' north of fence west and 9' east of centerline of CSAH 30
County Survey Disk in CP W 61.68'
County Survey Disk in 13" Maple WSW 105.0'
County Survey Disk in 15" Maple SW 137.76'
County Survey Disk in PP SW 97.0'
County Survey Disk in large CP E 39.2'
Punch hole in N end 15" CMP SE 29.18'
Punch hole in S end 15" CMP SE 49.72'
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor South on true line between sections 3 and 4. 39.73 chs. Set a quarter post. Burr Oak 8 in. N70ºE 37 lks. Burr Oak 8 in. N5ºW 162 lks. 79.73 chs. To section corner.

4-1892 Thomas Fraser (P. 483 No. 460), County Surveyor, states corner gone. Set a 3"x8"/18"x20" stone with cross as the corner on the section line and at proportionate Gov't measure.

10-1897 William Fraser (P. 612 No. 556), County Surveyor, found the stone P. 483. Set a stone at the 1/16th South midway and on line.

6-23-1976 County Surveyor, the Corner comes in a deep cut area on C.R. #30. Set a C.I.M. as the corner on line between North Sec. Cor. 3-4 and Sec. Cor. 3-4-9-10 and at double the distance from Sec. Cor. 3-4-9-10 over the 1/16th North (found).

9-30-1998 County Surveyor found CIM in good condition 6" deep in bituminous C.R. #30.

7-23-2003 County Surveyor found CIM down 0.5' in good condition.