Certificate of Location of Government Corner

ID#:510406 **Description:** 1/4 SEC COR 4 5 51 **Date Set:** 8/11/2003 **County:** Olmsted

Section: 04 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 0.8' SW of CP, 1' west of N-S fence and 1' south of E-W fence
Sign on CP 1/2' NE
This corner is located by GPS reference stations "Charlay A & B"

Corner History:

1853 Goverment notes Wm.A.Jones set 1/4-corner post at 40 chs from south. Total mile 79.79 chs or 2626.14' from north, 8" Burr Oak S81.5°E, 210 lks. 10" White Oak S89°W, 201lks.

10-1897 W.Fraser pg 612 no 556 sec 4 corner gone. Located temporary stake 1/3 distance -39.97 chs- from NW4 to 1/4-corner of sec 8+9. NOTE: THIS 1/4-CORNER SHOULD NOT HAVE BEEN SET 1/3 DISTANCE AS Gov't MEASUREMENT. N 1/2 IS 39.79 OR 21 SHORTER. MUST BE CHECKED.

7-25-2003 County Surveyor found nothing.

8-11-2003 County Surveyor dug 7 1/2' N-S by 6' E-W by 2' deep to clean clay and found nothing. Set 6' telspar with cast iron cap at surface at 1976 shot position. Set sign on C.P.