Certificate of Location of Government Corner

ID#:510604 **Description:** 1/4 SEC COR 6 7 51 **Date Set:** 12/5/1998 **County:** Olmsted

Section: 06 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' east of fence north and 1 1/2' north of fence east
Plastic disk in Brace post NNW 6.85'
Plastic disc in 24" Oak NE 23.55'
Plastic disk in 28" Oak WSW 42.38'

Corner History:

Gov't notes 8/1853: Set 1/4-sec-post, 40 chs. 5" Burr Oak N32-1/2°W, 49 lks. 8" White Oak S42-1/2°W 18 lks. Brook 2 links wide runs south 9.7 chs.

5-1875 Hunter pg 278 no 275 found original stake standing Northwest bearing tree gone. Southwest bearing tree still standing, did not quite agree. Set stone 2x4x18" in place of old stake. Measurement west, N88°35'E 39.18 chs, east N89°E 40.04 chs.
1/16 west - set stake on line and proper measures.

10-1897 W.Fraser pg 610 no 555 found stone set pg 278 2x4x18". Set another long stone by its side. 1/16 south - found Hunters stake. Set stone by side. Hunters stake placed in unrecorded survey 10-1886. 1/16 east - set stone 5x18x20".

10-1997 Roger Brand and Associates found stone at 1/16th corner East. They doubled line and distance from East and set 1/2" pipe w/cap #8952 and took references.

12-5-1998 County Surveyor set Cast Iron Cap on telspar pipe at Roger Brand location.