Certificate of Location of Government Corner

ID#:510605 **Description:** W SEC COR 6 7 51 **Date Set:** 9/24/1973 **County:** Olmsted

Section: 06 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 0.7
The corner falls in centerline of CR 136, 3' south of fence west and in line with fence east
5/8" Iron E 60.0'
This corner is located by GPS measurement.

Corner History:

1853 Gov't Notes North between sections 7 and 12. 80.00 chs. Set section corner post. Burr Oak 6 in. S9ºE 503 lks. Burr Oak 6" N68ºE 359 lks.

7-1856 Thomas Hunter (P. 13 No. 20), Co. Surveyor, used corner.

5-1875 T. Hunter (P. 278 No. 275) found original corner and SE bearing tree standing. Set 2"x12"x23" stone with stake by its side.

5-1880 John Fraser (P. 367 No. 358), County Surveyor, used corner to set 1/16 east.

9-24-1973 County Surveyor dug and found stake and 18" of 23" stone. Set 10" of base of stone in original place with 5/8" rod on east side and pieces of stone on all other sides. Set CIM over all.

7-31-1996 County Surveyor found CIM in good condition.

12-17-1998 County Surveyor found CIM in good condition.

6-4-2009 County survey crew found CIM in good condition.

2-14-2011 County survey crew found CIM in good condition.