Certificate of Location of Government Corner

ID#:510804 **Description:** 1/4 SEC COR 8 17 51 **Date Set:** 12/27/1982 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 11W **Monument Description:** 1" square pipe with cap RLS #8952

Reference Ties:

The corner falls 2.2' west of centerline of CSAH 10 and 2.1' WSW of County highway disk PI rod
Punch hole in N end CMP NW 43.50'
Punch hole in S end CMP SW 43.26'
Punch hole in S end CMP SE 46.27'
Punch hole in N end CMP NE 44.78'
County Survey Disk in NW side PP #47577 NE 54.88'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: William A. Jones, Deputy Surveyor West on true line between Sections 8 and 17. 39.92 chs. Set quarter section post. Burr Oak 8 in. N46ºW 50 lks. Burr Oak 10 in. S10°W 49 lks. 79.84 chs. To section corner.

9-1857 E.P. Bircher, Surveyor, per T. Hunter, Deputy, (Old Road Book, Road No. 24) used the corner to survey the road running North and South.

5-1875 Thomas Hunter, County Surveyor (Book A, Page 279, No.276, and Old Fieldbook 4, Pages 52 53) "1/4 post missing, the N.W.B.T. standing, the S.W. grubbed out. On digging in center of road, at point indicated by field notes, from the witness tree standing, we found the remains of two stakes standing c1ose together left them as found and refilled hole dug." Plat shows a measure East of 39.75 chs . to Sec. Cor. 8 9 16 17. He used the corner to set the Center 8, a boulder stone 17"x10"x9" at intersection of the 1/4 lines.

6-1899 William Fraser, County Surveyor, (Book A, Page 656, No.585, and Old Fieldbook 9, Pages 37 42) Found N.W. B.T. standing and from said tree according to U.S. Field notes found remains of old stake in center of road. Set stone 34x20x3 inches in place of stake." He used the corner to stake the centerline of the road running south.

5-1900 Robert Fraser, Deputy County Surveyor, (Book A, Page 681, No. 606, and Old Fieldbook 15, Pages 77 82) "Found stone set by Wm. C. Fraser from N.W. wit. tree. Tested and found correct. Stone in center of cross roads." He used the corner to set a property corner stake 6.74 chs. North and on line to recorded boulder found at the Center 8 (North 39.72 chs.) and a stake 29.675 chs. East and on line to Sec. Cor. 8-9-16-17 as located this survey.

6-1902 William Fraser, County Surveyor, (Book B. Page 40) used a stake set near Center 17 in Survey 585 for the N S 1/4 line and intersected E W 1/4 line to set the Center 17, a stake.

1935 County Highway Department (C.H.D. Book 75, Page 5) found boulder at corner (52 58.9 South of 1/4 Cor. 5 8).

1935 County Highway Department (C.H.D. Book 83, Page 18) shows "stone mon." at the corner.

6-14&25-1976 County Surveyor removed County Highway Department 0.5" rod and dug for corner. Found boulder found by County Highway Department in 1935 and found Fraser's stone lying flat on the North side of the boulder. Could not find the location where Fraser's stone had stood. The boulder was appx. 2' West and 1' North of the County Highway Department rod. Dug at the Center 17 and found old stake believed to be the stake set by Fraser in 1902 as Corner.

7-2-1976 County Surveyor set 0.5x23" rod as the corner on line from the S.1/4 Cor. 17 (found) over the Center 17 (found) and at prorated Will Fraser measure from the Center 17 (prorated against Fraser's measure from the S. 1/4 cor. 17 to the Center 17 as measured this survey).

8-8-1977 County Surveyor took additional references before road grading.

5-1982 County Surveyor, after road graded, the County Surveyor found remaining references not reliable to reset the corner E W. Set the corner at the intersection of the line from the S. 1/4 Cor. 17 over the Center 17 and the remaining references. Took additional references.

12-27-1982 County Surveyor set a 1" square pipe w/cap as Corner in new concrete on CR 10 from references taken 5-1982.

11-8-2006 County Surveyor found 1" square pipe w/cap at surface in good condition.