Certificate of Location of Government Corner

ID#:510805 **Description:** SEC COR 7 8 17 18 51 **Date Set:** 6/21/1976 **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 8' west of centerline of N-S twp road and 2' south of centerline of E-W twp road
County Survey Disk in PP #2103 NW 47.14'
County Survey Disk in PP #2104 NE 162.45'
Punch hole in N end 24" CMP NE 65.8'
Punch hole in S end 24" CMP SE 63.7'
Punch hole in E end 24" CMP SE 64.87'
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 17 and 18. 80.00 chs. Set post-corner to sections 7,8,17&18 Burr Oak 8 in. N82ºW 55 lks. Burr Oak 8 in. S42&3/4º 305 lks. Burr Oak 4 in. N57ºE 174 lks. Burr Oak 5 in. S53ºE 131 lks.

5-1880 John Fraser (P. 367 No. 358), County Surveyor, could find no corner. Set a stone 2"x4"x18" as the corner on the testimony of the local settlers.

9-25-1973 County Surveyor dug for the corner but did not find anything.

6-21-1976 County Surveyor dug again with the backhoe and found a stake 7' deep with 2 small pieces of limestone around it. Set a 1/2"x18" rod in the stake hole. Set a C.I.M. over a 1/2"x20" rod at the road surface.

11-8-2006 County Surveyor found CIM down 1' in good condition.