Certificate of Location of Government Corner

ID#: 510809 **Description:** SEC CEN 8 51 **Date Set:** **County:** Olmsted

Section: 08 **Township:** 105N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-22-1875 Thomas Hunter, County Surveyor, (Book A, Page 279, Survey No. 276) set 9"x10"x17" boulder stone in road at intersecting quarter lines.

10-11-1897 William Fraser, County Surveyor, (Book A, Pages 610-611, Survey No. 555) found boulder. Removed and set 3"x5"x18" limestone below with boulder on top. 1/16th North set short stake with an iron stake midway and on line at 19.99-1/4 chains (1319.51') to North 1/4. 1/16th West set 3"x10"x24" stone midway and on line at 20.01-5/8 chains (1321.07') to West 1/4. 1/16th Center of NW 1/4 set 3"x6"x17" stone over stake at intersecting sixteenth lines.

5-21-1900 Robert Fraser, Deputy County Surveyor, (Book A, Pages 681-682, Survey No. 606) found boulder stone.

1935 County Highway Department, (Book 75, Page 4) found boulder in roadbed. P.I. Sta. 26+38.6. RPs - Spike in fence post SE 57.9', Spike in telephone pole NE 96.2', Spike in fence post SW 36.6', Spike in power pole NW 81.3'

9-19-1935 County Highway Department, (Book 83, Page 18) updated ties. RPs - Spike in oak W 79.1', Spike in telephone pole SE 82.2', Spike in power pole NW 78.9'

6-23-1976 County Surveyor visited area. Corner location falls on top of hill in 4' cut. Dug with backhoe and found road cut into clean clay. Found nothing.

9-26-1978 Roger Brand, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plat No. 6.

2-7-1987 Jerome Schwarz used computed center at intersecting quarter lines.