Certificate of Location of Government Corner

ID#:510905 **Description:** SEC COR 8 9 16 17 51 **Date Set:** 5/1/2007 **County:** Olmsted

Section: 09 **Township:** 105N **Range:** 11W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 15' north of south lane fence, 10' east of fence north and 2 1/2' north of fence east
County Survey Disk in 12" Walnut NW 23.43'
County Survey Disk in 12" Walnut SW 39.87'
This corner is located by GPS reference stations "Old Road A & B"

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 16 and 17. 80.00 chs. Set post-corner to sections 8,9,16&17 White Oak 15" N75ºE 152 lks. White Oak 6" N7ºW 19 lks. White Oak 7" S131/2ºW 75 lks. Burr Oak 6" S20ºE 125 lks.

5-1875 Thomas Hunter (P. 279 No. 276), County Surveyor, reset this corner with a marked stake from one standing bearing tree and 2 bearing tree stumps.

4-1878 T. Hunter (P. 340 No. 334) found corner P. 340.

5-21-1900 Robert Fraser (P. 681 No. 606), County Surveyor, reset the corner with an iron kingbolt from the stumps of the bearing trees. Measured West to 1/4 Cor. 8-17. Measured North to 1/4 Cor. 8-9.

6-1902 William Fraser (P. 40B), County Surveyor, found an iron stake as the corner. Set 1/4 Cor. 16-17 midway and on line.

6-25-1976 County Surveyor corner comes in an old road, cut or washed down to bedrock. Searched for Robert Fraser's iron with the electronic metal detector but could find nothing.

7-2-1976 County Surveyor set a 3/4"x18" shaft (up 8") as the corner in the center of the old road. The N-S location of this corner was determined by doubling the measure from the calculated N-S location of Sec. 16-17-20-21 (determined by the line from Sec. Cor. 17-18-19-20 (found) over 1/4 Cor. 16-17 (determined by the line from 1/4 Cor. 17-18 (found) over the Center of Sec. 17 (found). The corner is located E-W at proportionate Robert Fraser measure from 1/4 Cor. 8-17 (prorated against his measurement from 1/4 Cor. 8-9 (found) to the N-S location of Sec. Cor. 8-9-16-17 as previously determined).

8-29-2003 County Surveyor found nothing.

5-1-2007 County Surveyor found SW & NW witness trees from (1976) which matched our set out location from previous traverse. Set 1" square pipe w/cap RLS #15809 driven to refusal in bedrock.