# Certificate of Location of Government Corner

**ID#:**511004 **Description:** 1/4 SEC COR 10 15 51 **Date Set:** 11/13/1998 **County:** Olmsted

**Section:** 10 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls under N-S fence and 5.3' north of wood fence post in fence line
Post w/sign 2' south
This corner is located by GPS reference stations "Flanary I & II"

**Corner History:**

Gov't notes: Set 1/4-sec-post, 40 chs. 10" Burr Oak S54ºE, 126 lks. 6" Burr Oak N70ºW, 135 lks.

4-1878 T. Hunter pg 339 no 333 sec 15 found northwest bearing tree standing. Others gone. Found old stake at 140 lks instead of 135 lks. Set stone 2x4x14". 1/16 S - set stone 2" x 3/10' x 24".

4-1892 Thomas Fraser pg 477 no 456 sec 10-11 found stone pg 339. 1/16 N - set stake

11-12-1998 County Surveyor dug for stone at T. Hunter measure from center of section 15 (found nothing).

11-13-1998 County Surveyor dug to cover kink in E-W section line shown in book A by T. Fraser. Found stone 2" x 4" x 14" set by T. Hunter in (1878) over stake mark. Set Cast Iron Cap on telspar pipe at Gov't stake location used by T. Hunter.