Certificate of Location of Government Corner

ID#:511006 **Description:** 1/4 SEC COR 9 10 51 **Date Set:** 9/8/1975 **County:** Olmsted

Section: 10 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' west of centerline of N-S twp road and in line with main fence west
County Survey Disk in CP W 31.8'
Punch hole in N end CMP NE 34.66'
Punch hole in S end CMP SE 33.63'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes W.A. Jones North between sections 9 and 10. 40.00 chs. Set quarter section post. Deposited stone 6"x4"x3". Made mound and dug trench and pits.

4-1875 Thomas Hunter (P. 340 No. 334), County Surveyor, found stone with stake by side in center of road.

4-1892 Thomas Fraser (P. 477 No. 456) found stone P. 340.

1936 county highway department (B. 85) assumed corner. Set bridge spike.

9-8-1975 County Surveyor dug with backhoe and found 3"x4"x13" limestone 2' deep. Set C.I.M. over 1/2" square by 12" iron as corner with stone along side. Found Co. Hwy. Dept. bolt 1.7' S and 2.2' E (removed).

9-30-1998 County Surveyor found CIM in good condition 1' deep in N-S twp road.