Certificate of Location of Government Corner

ID#:511105 **Description:** SEC COR 10 11 14 15 51 **Date Set:** 9/9/1975 **County:** Olmsted

Section: 11 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner is down 1.2'
The corner falls in cultivated field 80' NE of centerline of CSAH 30
County Survey Disk in E side PP #2472 NNW 92.2'
This corner is located by GPS reference stations "South Shoulder & North Shoulder"

Corner History:

9-1853 Gov't Notes William A. Jones North between sections 14 and 15. 80.00 chs. Set post corner to sections 10,11,14 and 15 Burr Oak 14" S51/2ºE 803 lks. Red Oak 8" S101/2ºW 580 lks.

4-1878 Thomas Hunter (P.339 No. 333), County Surveyor, found remains of old stake from bearing tree stump. Set stone 31/2"x9"x20" in its place. After setting 1/4 Cor. 10-11 midway and on line, set 1/16 N of Sec. Cor. 10-11-14-15 midway and on line.

4-1892 Thomas Fraser (P. 477 No. 456), County Surveyor, accepted stone answering Hunter's description and avered as Hunter's stone by a Mr. Ketlam as corner.

1935 County Highway Department (B. 85 P. 73) found limestone and small boulders around it. Set 1/2" rod riser.

11-1961 County Highway Department set C.I.M. over corner found 1935.

9-9-1975 County Surveyor corner now lies in cultivated field. Dug 5'x5' to clay. Found some wood pieces and dark spot (possible stake or corner post location) at computed corner location. Set C.I.M. (deep) over 1/2"x9" pipe as corner by line and measure of 1/16N (found) and Sec. Cor. 2-3-10-11 (found) which came over dark spot in clay.

9-18-1998 County Surveyor found CIM in good condition down 1.2' in corn field.

2-15-2011 County survey crew found CIM in good condition