Certificate of Location of Government Corner

ID#: 511109 **Description:** SEC CEN 11 51 **Date Set:** 4/4/2006 **County:** Olmsted

Section: 11 **Township:** 105N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1/2" pipe w/cap RLS #21940

Reference Ties:

The monument is at the surface
This corner is located by GPS measurement

Corner History:

4-6-1892 Thomas Fraser, County Surveyor, (Book A, Pages 477-479, Survey No. 456) set temporary stake at intersecting quarter lines. 1/16th North set temporary stake midway and on line at 19.87-15/16 chains (1312.04') to North 1/4. 1/16th West set temporary stake midway and on line at 19.93-7/8 chains (1315.96') to West 1/4. 1/16th Center of NW 1/4 set 4"x10"x24" stone with glass at intersecting sixteenth lines.

12-12-2005 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

4-4-2006 GGG set 1/2" pipe w/cap #21940 at intersecting quarter lines.

7-6-2006 GGG found and used 1/2" pipe w/cap at intersecting quarter lines.

8-3-2006 GGG found and used 1/2" pipe w/cap at intersecting quarter lines.

9-1-2010 M. James Associates used computed center at intersecting quarter lines.

9-2-2010 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section.

2-18-2011 County Survey Crew found 1/2" pipe with cap RLS #21940 at the surface in good condition and measured its position using GPS. Based on the county's section breakdown, the 1/2" pipe w/cap, as located by GPS in 2011, falls 0.15' north and 0.13' east of the computed center.

1-15-2014 G-Cubed used computed center at intersecting quarter lines.