Certificate of Location of Government Corner

ID#:511206 **Description:** 1/4 SEC COR 11 12 51 **Date Set:** 8/25/1975 **County:** Olmsted

Section: 12 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of fence east, 1 1/2' west of fence north and 13' north of centerline of twp road east
County Survey Disk in S side stub PP E 61.8'
County Survey Disk in N side PP #2553 SE 217.1'
This corner is located by GPS reference stations "Wava & Kjosa"

Corner History:

9-1853 Gov't Notes W.A. Jones, Deputy Surveyor North between sections 11 and 12. 40.00 chs. Set quarter section post. Built mound, dug trench and pits as per instructions. Planted cherry seeds N.W. and S.E.

5-1889 John Fraser (P. 432 No. 419), County Surveyor, states corner plowed out. Set stone 3"x10"x30" midway and on line.

4-1892 Thomas Fraser (P. 477 No. 456), County Surveyor, used corner to set center of section.

10-1897 William Fraser (P. 613 No. 557), County Surveyor, found corner P.432.

8-25-1975 County Surveyor dug in ditch on N. side of E.W. driveway road. Found remaining 12" of 10"x3"x30" recorded stone 21/2' deep. Set 3/4" rod on east side and flat iron on west side with scrap iron and junk around. Set C.I.M. over all.

9-15-1998 County Surveyor found CIM down 0.8' in good condition.

4-4-2006 GGG, Inc. found and used monument in section 11 survey.