Certificate of Location of Government Corner

ID#:511404 **Description:** 1/4 SEC COR 14 23 51 **Date Set:** 12/13/2004 **County:** Olmsted

Section: 14 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 6' south of break line between fields
Traverse point Wadewitz A E 57.62'
This corner is located by GPS reference stations "Wadewitz A & B"

Corner History:

Gov't notes: set post and stone (no size) mound & pits

6-1873 Hunter pg 230 no 233 sec 22-23 found mound by side of fence with stone in center of mound. 1/16 E - set temporary stake 1/16 W - set permanent stake in road 1/16 S - set permanent stake in road 1/16 center NE1/4 sec 23 set stake at intersecting lines 1/16 center NW 1/4 sec 23 set stake at intersecting lines

12-6-2004 County Surveyor dug hole 4'x3'x4' deep centered on T. Hunter's computed position from GPS and traverse data. Found nothing. The area is on west side of waterway north in deep filtered area. Fence line was cleared and grubbed extensively 15-20 years ago.

12-13-2004 County Surveyor set 6' telspar pipe w/cast iron cap down 1.1' at T. Hunter's prorated measure from GPS and traverse data.