Certificate of Location of Government Corner

ID#:511406 **Description:** 1/4 SEC COR 14 15 51 **Date Set:** 11/24/2004 **County:** Olmsted

Section: 14 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2' south of E-W fence
Post w/sign 2' north
This corner is located by GPS reference stations "Donald A & B"

Corner History:

Gov't notes: set post and stone 6x6x2", mound & pits.

4-1878 T. Hunter pg 339 no 333 sec 15 found remains of old stake by side of old fence post. Set boulder stone in its place. 1/16 N - set stone 2x7x16" 1/16 W - set temp point 1/16 S - set temp point

1956 County Hwy. Dept. Books 215-272 found 4x10x28" limestone, also stone 660' E, no ties.

11-1983 1/16 E - County Surveyor found county highway department CIM in centerline N-S-road and 10' S of fence West and 7' N of centerline road farther East.

11-25-1998 County Surveyor dug looking for T. Hunter boulder stone set in 1878 and Co. Hwy. Dept. 4" x 10" x 28" limestone found in 1956. Found 1" drill steel 40" long beside stone 2" x 7/14" x 18" long next to corner post. Found stake mark with wood pieces in it at clay line 2' deep. The stake mark is .5' South and .15" East of drill steel. Set drill steel in stake hole.

10-11-2002 County Surveyor found 1" iron rod in good condition up 0.6'.

11-14-2002 660' E: County Surveyor computed location of stone found by county highway department in 1956. Location fell 9' South of existing E-W fence in plowed field. Dug from there to 6' North to cover lines from East. Old woven wire fence was 8' North, down under sod. Found nothing.

1/16th W: County Surveyor walked to area. Now common land on North and South side of E-W fence. Found 3 corner posts to fence E-W. Between the 3 posts found stone 3x10x24 standing vertically.

11-16-2004 1/16th W: County Surveyor dug for T.H. stone set in 1878. Found stone of T.H. record 2"x7"x16" down 0.6' in good condition. The stone falls 3 1/2' south of E-W fence and 11' east of newer corner post in E-W fence and 10.5' east of spike shot in 2002. Set iron ring around stone with a flat iron vertical on east side.

11-24-2004 County Surveyor set cast iron cap on telspar pipe as corner at drill steel location in stake mark found in 1998.