Certificate of Location of Government Corner

ID#:511605 **Description:** SEC COR 16 17 20 21 51 **Date Set:** 7/30/2007 **County:** Olmsted

Section: 16 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 17' south of centerline of E-W twp road
County Survey Disk in N side 24" Cottonwood E 77.43'
This corner is located by GPS reference stations "Gerald A & B"

Corner History:

Gov't notes: set section-post, 80 chs, dug trench. 12" Burr Oak, N75-1/2ºE, 187 lks. 12" Burr Oak, N88-3/4ºW, 72 lks.
13" Burr Oak, S66-3/4ºW, 52 lks.

4-1878 Hunter pg 338 no 332 found stake standing and tested stumps of NW & SW bearing trees.

6-1899 W. Fraser pg 656 no 585 found bearing tree stumps and set a stone 2.5x9x28".

6-1902 W. Fraser pg 40 Bk"B" found stone as corner pg 656. Measured N to stake set 39.82-1/2 chs.

11-13-2006 County Surveyor did not find anything.

7-18-2007 County Surveyor visited area, did not find anything.

7-30-2007 County Surveyor set 4 1/2' telspar pipe w/CIC up 0.3' from computed coordinates. CSD with 60d nail in N side of 24" Cottonwood E 77.43'.