Certificate of Location of Government Corner

ID#:511706 **Description:** 1/4 SEC COR 17 18 51 **Date Set:** 6/18/1976 **County:** Olmsted

Section: 17 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and in line with fences east and west
County Survey Disk in PP #2131 NW 93.98'
County Survey Disk in PP #2132 SW 218.75'
This corner is located by GPS measurement

Corner History:

8-1853 Gov't Notes William A. Jones, Deputy Surveyor North between sections 17 and 18. 40.00 chs. Set quarter section post. Deposited stone, dug trench and pits, and made mound. Planted Cherry seeds N.E. and S.W.

5-17-1975 Thomas Hunter (P. 276 No. 273), County Surveyor, found stone in the center of the road.

6-1902 William Fraser (P. 40B), County Surveyor, found stone.

6-18-1976 County Surveyor dug with the backhoe and found a 4"x11" / 16"x20" limestone 1' deep in the centerline of the N-S road and in line with the fences East and West. Broke off top 1/2 of the stone to make room for the C.I.M. Also set rods on the East and West sides of the stone.

11-8-2006 County Surveyor found CIM down 0.5' in good condition.