Certificate of Location of Government Corner

ID#: 511709 **Description:** SEC CEN 17 51 **Date Set:** **County:** Olmsted

Section: 17 **Township:** 105N **Range:** 11W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

1/2" rod E 109.44'
1/2" rod E 225.19'
This corner is located by GPS reference stations "Ref Iron 511709 A & B"

Corner History:

6-1857 E.P. Bircher, by Thomas Hunter, Road #24 Survey, measured south, from North 1/4, 39.50 chains to center and measured west 39.14 chains to West 1/4.

6-9-1899 William Fraser, County Surveyor, (Book A, Pages 656-657, Survey No. 585) set stake on line and 40.00 chains south of North 1/4 as a road building guide.

6-5-1902 William Fraser, County Surveyor, (Book B, Page 40) found stake. Reset stake at intersecting quarter lines. 1/16th West set stake midway and on line at 19.81 chains (1307.46') to West 1/4.

6-25-1976 County Surveyor dug and found old stake in clay down 3.5'. Set spike in stake with junk around. The corner falls 4' north of fence east, 1-1/2' north of fence west and 1/2' west of centerline.

6-29-1976 County Surveyor set 1/2"x24" rod at surface over stake. RPs - CSD in south side fence post WSW 33.65', CSD in south side corner post ESE 37.97', CSD in east side PP SW 143.40', CSD in east side PP NW 193.87'.

8-8-1977 County Surveyor found 1/2" rod at surface in good condition. Referenced for road construction. RPs - 1/2" rod E 109.44' on line to 1/2" rod E 225.19'.

9-26-1978 Roger Brand, County Surveyor, used computed center at intersecting quarter lines for Olmsted County Highway Right of Way Plat No. 5.

5-8-1979 Yaggy Associates set pk nail at surface from County Surveyor ties.

5-14-1982 County Surveyor found 1/2" rods set as references in good condition. All other ties are gone.

11-15-1999 GGG used computed center at intersecting quarter lines.

12-24-2004 Blumentritt Land Surveying used computed center at intersecting quarter lines.

4-27-2007 County Survey Crew visited area of corner and found nothing. Found 1/2" rods set as references and measured their positions using GPS.

12-13-2010 Jerome Schwarz used computed center at intersecting quarter lines.