Certificate of Location of Government Corner

ID#:511805 **Description:** W SEC COR 18 19 51 **Date Set:** 10/8/1976 **County:** Olmsted

Section: 18 **Township:** 105N **Range:** 11W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is at the surface
The corner falls 4 1/2' south of E-W fence and 15' west of fence north
County Survey Disk in S side CP NE 15.70'
County Survey Disk in NE side 15" Burr Oak SE 17.53'
County Survey Disk in W side 15" Burr Oak SSE 127.55'
County Survey Disk in N side 26" Burr Oak SW 41.30'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor North between sections 19 and 24. 80.00 chs. Set post corner to sections 13,18,19 & 24. Burr Oak 10 in. S9°E 164 lks. Burr Oak 12 in. SlOºW 68 lks.

5-17-1875 Thomas Hunter (P.276 No.273), County Surveyor, could not find the corner. Set a 3"x6"x16" stone as the corner from the S.E. bearing tree.

5-23-1875 Hunter (P.277 No.274) found the corner P.276.

10-8-1976 County Surveyor dug for the corner and found the recorded stone 18" deep. Drove a 1/2"x2' rod on the North side of the stone and set a C.I.M. over the stone.

3-21-2011 County survey crew found CIM in good condition.